PANEL VAN GAZelle NEXT



- \square Volume of cargo space up to 15.5 m³
- Prolonged wheel base
- Modified rear drive axle
- Disk brakes of rear wheels
- Enforced rear suspension with lower dual-rates
- □ High level of equipage in the basic scope of supply

TECHNICAL CHARACTERISTICS

| Parameters | Vehicle model | |
|------------------------------------------------------------------------|---------------|--------|
| | | C46R02 |
| Passenger capacity | 3 | 7 |
| Gross vehicle weight, kg | 4600 | |
| Curb weight, kg | 2636 | 2727 |
| Curb weight, suitable for each vehicle axle, kg: | | |
| front | 1650 | |
| rear | 3300 | |
| Road clearance, mm | 170 | |
| Minimum turning radius on outer front wheel track, m | 6.8 | |
| Fuel consumption rate at constant speed, I/100 km: | | |
| 60 km/h | 9.0 | |
| 80 km/h | 11.5 | |
| Maximum vehicle speed on the horizontal site of the even highway, km/h | 130 | |
| Overhang (with load), in degrees: | | |
| front | 22 | |
| rear | 12 | |
| Maximum ascend with full load, % | 26 | |

| Engine model | ISF2.8 | |
|---------------------------------------------|-------------------------------|--|
| Ecological class | Euro-5 | |
| Туре | Turbo-diesel with intercooler | |
| Number and arrangement of cylinders | 4, in a row | |
| Cylinders capability, I | 2.8 | |
| Ratio of compression | 16.9 | |
| Maximum power, kW (HP) | 102.7 (139.6) | |
| Rotation at crankshaft speed, rpm | 3300 | |
| Maximum torque, Nm | 320 (32.6) | |
| at crankshaft speed, rpm | 1400-2700 | |
| Crankshaft rotation speed in idle mode, rpm | | |
| Minimum, rpm | 750±50 | |
| Maximum, rpm | 4500 | |

C45R02





